



Capacity Kg	Lifting Height m	Model	Lifting Speed	Hoist Motor	Travel Speed	Trolley Motor	Hoist duty		Trolley duty		H (mm)	C (mm)	Mini track space(Smin:mm)
			m/min	KW	m/min	KW	FEM	ISO	FEM	ISO			LH=6m
3200	6,9 12,15,18	ESD032	5/0.8	3.2/0.45	20/5	0.25*2	2M	M5	2M	M5	210	556	1200
5000	6,9 12,15,18	ESD050	5/0.8	6.1/1	20/5	0.37*2	2M	M5	2M	M5	260	596	1400
6300	6,9 12,15,18	ESD063	5/0.8	6.1/1	20/5	0.37*2	1Am	M4	2M	M5	260	596	1400
8000	6,9 12,15,18	ESD080	5/0.8	9.5/1.5	20/5	0.37*2	3M	M6	2M	M5	325	750	1400
10000	6,9 12,15,18	ESD100	5/0.8	9.5/1.5	20/5	0.37*2	2M	M5	2M	M5	325	750	1400
12500	6,9 12,15,18	ESD125	4/0.6	12.5/2	20/5	0.55*2	1Am	M4	2M	M5	325	750	1400
16000	6,9 12,15,18	ESD160	4/0.6	16/2.6	20/5	0.55*2	2M	M5	2M	M5	400	920	1400
20000	6,9 12,15,18	ESD200	4/0.6	16/2.6	20/5	0.55*2	1Am	M4	2M	M5	400	920	1400
25000	6,9 12,15,18	ESD250	3.3/0.8	20/5	20/5	0.75*2	3M	M6	2M	M5	400	920	1700
32000	6,9 12,15,18	ESD320	3.3/0.8	20/5	20/5	1.1*2	2M	M5	2M	M5	325	750	1700
40000	6,9 12,15,18	ESD400	0~4	38	20/5	1.5*2	1Am	M4	2M	M5	325	750	1700
50000	6,9 12,15,18	ESD500	0~4	38	20/5	1.5*2	2M	M5	2M	M5	325	750	1700